

DISPLAY
 Analog Filters OUT-OUT
 Straight Gain
 + 18 + 0 - 20 - 2
 Tapes HTL 1082
 HTL

REQ. N°	L-188
Section N°	1092 C
System Code	MSTV 2
Assembled By	<i>LM</i>
Checked by	<i>RM</i>

△ S.E.

LINE B 423
 SP 6415

98 Meters 97 96 95 94 93 Meters 91
 8119 8130 8140 8150 8160 8170 8180 8190 8200 8210 8220 8225

SHOOTING PARAMETERS

12 Fold Off End
 Shot by GSI PTY 906
 Cable Length 2400 m
 Group Interval 100 m
 Shot Point Interval 100 m
 Average Shot Offset 100 m
 Charge Size 50 lb
 Average Seis Depth 12 m

RECORDING PARAMETERS

System 9000
 Record Length 50
 Sample 2ms
 GAGC Trip 0.47s Rate 80db/s
 Init 43 db Final 100db
 Filters Hi 75 cps 24db/oct
 Lo 8cps 24db/oct
 2ms Anti Alias Filtering

SEIS EDIT & NMO

TAR
 4.0 db/sec
 From 0 sec to 4.0 sec

Water Velocity 1522 m.p.s
 Replacement Vel. 1522 m.p.s

DECONVOLUTION

Time variant ARD I
 Filter Length 220 m sec
 Gate Length 2.20 sec
 No of Gates/Trace 2
 Initial times, Gate No 1 :-
 Tr 1 7 sec, Tr 2 40-504 sec
 Final times, Gate No 2 :-
 Tr 1 5.0 sec, Tr 2 43804 sec

6-FOLD STACK

Optimum Wide Band Stack
 RNMO Yes Diversity Stack Yes
 First Break Suppression
 T₁ 0 sec T₄ 1.4 sec
 T₂ 0.8 sec T₅ 1.6 sec
 T₃ 1.2 sec T₆ 1.8 sec

