


SHOOTING PARAMETERS
 6-Fold Off End
 Shot by GSI PTY 910
 Cable Length 1600 m
 Group Interval 67 m
 Shot Point Interval 134 m
 Average Shot Offset 134m
 Charge Size 50 lb
 Average Seis. Depth 17 m

RECORDING PARAMETERS
 System 9,000
 Record Length 5.0 secs
 Sample 2 ms
 GAGC Trip 0.6% Rate 80db/s
 Int. 33 db Final 100 db
 Filters Hi 75 cps 24 db/oct
 Lo 8 cps 24 db/oct
 2ms Anti Alias Filtering

SEIS EDIT & NMO
 TAR
 $\kappa = 4.0$ db/sec
 Fram 0 sec to 4.0 sec
 Water Velocity 1500 mps
 Replacement Vel 1500 mps

DECONVOLUTION
 Time Invariant ARD II
 Filter Length 212 msec
 Gate Length 2400 msec
 No of Gates/Trace 2
 Initial times, Gate No 1
 Tr1 1.1 sec, Tr 24 0.3 sec
 Final times, Gate No 2
 Tr1 4.7 sec, Tr 24 5.9 sec

6-FOLD STACK
 Optimum Wide Band Stack
 RNMO Yes Diversity Stack Yes
 First Break Suppression
 T₁ 0 sec T₂ 1.2 sec
 T₃ 0.6 sec T₄ 1.4 sec
 T₅ 1.0 sec T₆ 1.6 sec



DISPLAY	REQ. N°	L- 2212
Analog Filters OUT-OUT	Section N°	4183 C
Straight Gain	System Code	MSTV 2
+ 12 + 4 - 20 = - 4	Assembled by	<i>[Signature]</i>
Tape HTL 4330	Checked by	<i>[Signature]</i>

