997-11-50 **AGIP**

OFFSHORE ITALIA

ZONA F

SW 1 — LINEA F-75-101 — NE 620

1 km

COMPAGNIE GENERALE DE GEOPHYSIQUE

DIGITAL PROCESSING P5

TIME ORIGIN: Source and cable depth

STACK 4800 %

Boat motion

389 Date: MARCH 10.76 Checked

PROCESSING SAMPLING RATE 4 ms

1 AMPLITUDE RECOVERY
2 WAPC(stabilization by vaporchoc signal)
3 MUTING
4 DECONVOLUTION 240 ms windows 500 - 2300 ms / Below 1900 - 3600 ms sea bottom
5 VELOCITY ANALYSIS (VA)
6 RMS CORRECTIONS (LINEAR INTERPOLATION BETWEEN VELOCITY FUNCTIONS)
7 STACK 4800 %
8 TIME VARIANT FILTER (Origin sea bottom)
9 TRACE EQUALIZATION
10 ANALOG DISPLAY

FIELD RECORDING SAMPLING RATE 4 ms

Ship GLORITA TIDE Shooting date: NOV/1975
Field recorder SN 338 filter 1/8-125
Floating point, sampling 4 ms
Streamer 2400 m (Depth 19 m)
groups 48 (group interval 50 m)
Geophones type HC 201 nr 48 / group
48 Fold coverage
Energy source VAPORCHOC (Depth 6 m)
SP Tr1 Streamer Tr48
330m MOTOROLA positioning

00363

F 75 058B A 432 — F 75 058B 431 — F 75 058B A 571

Water depth in meters

150 182 213 248 273 299 320

NO SOUNDINGS

TWT 1 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200 210 220 230 240 250 260 270 280 290 300 310 320 330 340 350 360 370 380 390 400 410 420 430 440 450 460 470 484 490 500 510 520 530 540 550 560 570 580 590 600 603 TWT

000 200 400 600 800 1000 1200 1400 1600 1800 2000 2200 2400 2600 2800 3000 3200 3400 3600 3800 4000 4200 4400 4600 4800 5000 5200 5400 5600 5800 6000

FROM SP 1 * TO SP * 1* | *FROM SP* 125* TO SP * 125* | *FROM SP* 241* TO SP * 241* | *FROM SP* 363* TO SP * 363* | *FROM SP* 485* TO SP * 485* | *FROM SP* 531* TO SP * 531* | *FROM SP* 603* TO SP * 721*

AV.VEL. IN M/S* | *AV.VEL.* IN M/S* | *AV.VEL.* IN M/S* | *AV.VEL.* IN M/S* | *AV.VEL.* IN M/S* | *AV.VEL.* IN M/S* | *AV.VEL.* IN M/S*

TWT							
000							
200	1606	1500	1503	1500	1500	1500	1500
400	1725	1500	1500	1500	1500	1500	1500
600	1778	1522	1509	1500	1500	1500	1500
800	1681	1576	1501	1500	1500	1526	1500
1000	2020	1642	1556	1520	1524	1606	1520
1200	2324	1761	1644	1588	1604	1659	1566
1400	2547	1883	1729	1649	1681	1752	1675
1600	2705	2048	1803	1716	1796	1888	1769
1800	2815	2171	1915	1799	1888	2052	1896
2000	2905	2262	2053	1892	1968	2239	2022
2200	2969	2378	2166	2000	2040	2307	2125
2400	3116	2563	2266	2177	2221	2371	2287
2600	3321	2742	2572	2339	2390	2630	2451
2800	3499	2961	2764	2421	2535	2744	4076
3000	3653	3150	2946	7646	2718	2966	3071
3200	3787	3316	3126	7843	2911	3143	3241
3400	3905	3462	3267	7017	3061	7798	3392
3600	4011	3592	3423	7172	3272	3436	7525
3800	4105	3708	3548	7310	3367	3562	3646
4000	4189	3812	3661	3434	3489	3674	3753
4200	4266	3907	3761	3547	3599	3776	3850
4400	4336	7997	3855	7649	3699	3868	3979
4600	4398	4072	3943	7743	3790	3952	4070
4800	4456	4144	4017	7829	3874	4029	4094
5000	4511	4212	4088	3987	3951	4099	4162
5200	4561	4271	4154	3980	4022	4163	4225
5400	4607	4328	4215	4048	4088	4225	4287
5600	4649	4380	4272	4110	4149	4282	4338
5800	4689	4429	4324	4168	4206	4334	4386
6000	4726	4475	4374	4223	4259	4383	4435

VARIABLE FILTER

997 1750 II

Frequency in Hz

0 8 12 22 32 48

76 78