997-11.50 **AGIP**

OFFSHORE ITALIA

ZONA F

W 568 **LINEA F.75-113** E 1

1 km

COMPAGNIE GENERALE DE GEOPHYSIQUE

DIGITAL PROCESSING P5

TIME ORIGIN: Source and cable depth

STACK 4800 %

Boat motion →

332 | Date: FEB 12.76 | Checked

PROCESSING SAMPLING RATE 4 ms

1 AMPLITUDE RECOVERY
2 WAPCO (stabilization by vaporchoc signal)
3 MUTING
4 DECONVOLUTION 240 ms
windows 500 - 2300 ms ↓ Below sea bottom
1900 - 3600 ms
5 VELOCITY ANALYSIS (VA)
6 NMO CORRECTIONS
(LINEAR INTERPOLATION BETWEEN VELOCITY FUNCTIONS)
7 STACK 4800 %
8 TIME VARIANT FILTER (Origin sea bottom)
9 TRACE EQUALIZATION
10 ANALOG DISPLAY

FIELD RECORDING SAMPLING RATE 4 ms

Ship GLORITA TIDE Shooting date NOV 1975
Field recorder SN 338 filter VB-125
Floating point, sampling 4 ms
Streamer 2400 m (Depth 19 m)
groups 48 (group interval 50 m)
Geophones type HC 201 nr 48 / group
48 Fold coverage
Energy source VAPORCHOC (Depth 6 m)
SP Tr1 Streamer Tr48
330m MOTOROLA positioning

00374

F.75.062 144

F.75.060 162

VA

NO SOUNDINGS

Water depth in meters

TWT 568 550 540 530 520 510 500 490 48 470 460 450 440 430 420 410 400 390 380 370 360 350 340 330 320 310 300 290 280 270 260 250 240 230 220 210 200 190 180 170 160 150 140 130 120 110 100 90 80 70 60 50 40 30 20 10 1

000 200 400 600 800 1000 1200 1400 1600 1800 2000 2200 2400 2600 2800 3000 3200 3400 3600 3800 4000 4200 4400 4600 4800 5000 5200 5400 5600 5800 6000 6200 6400 6600 6800 7000

*FROM SP FROM SP FROM SP FROM SP FROM SP FROM SP FROM SP
* 4 428* 430* 151* 244* 143* 1*
* TO SP * TO SP * TO SP * TO SP * TO SP * TO SP * TO SP
* 428* 430* 151* 244* 143* 1*
*AV.VEL.*AV.VEL.*AV.VEL.*AV.VEL.*AV.VEL.*AV.VEL.*AV.VEL.*
* TI M/S* TI M/S* TI M/S* TI M/S* TI M/S* TI M/S* TI M/S*

000						
200	1500	1500	1500	1500	1500	1500
400	1500	1500	1500	1500	1500	1500
600	1500	1500	1500	1500	1500	1500
800	1500	1500	1500	1500	1500	1500
1000	1500	1500	1500	1500	1500	1500
1200	1500	1500	1500	1500	1500	1500
1400	1550	1560	1516	1538	1500	1500
1600	1601	1630	1556	1586	1538	1500
1800	1640	1670	1601	1658	1595	1544
2000	1747	1718	1656	1723	1655	1596
2200	1824	1673	1745	1785	1745	1650
2400	1846	1724	1811	1915	1842	1732
2600	1934	1765	1867	2076	1953	1803
2800	2043	2010	1958	2134	2022	1866
3000	2119	2145	2071	2282	2136	1958
3200	2210	2228	2251	2424	2235	2110
3400	2340	2488	2422	2577	2332	2228
3600	2450	2687	2581	2756	2399	2333
3800	2535	2847	2760	2916	2578	2422
4000	2745	2934	2912	3061	2739	2575
4200	2973	3128	3049	3191	2885	2720
4400	3206	3246	3174	3310	3018	2868
4600	3401	3360	3289	3418	3139	2996
4800	3588	3467	3393	3517	3246	3113
5000	3676	3575	3489	3608	3351	3220
5200	3758	3642	3578	3693	3446	3318
5400	3833	3722	3661	3771	3533	3411
5600	3904	3798	3737	3843	3614	3496
5800	3969	3867	3809	3911	3689	3576
6000	4030	3929	3874	3974	3759	3650
6200	4087	3987	3937	4032	3825	3719
6400	4141	4045	3995	4088	3887	3784
6600	4191	4099	4049	4140	3945	3845
6800	4238	4149	4101	4188	3999	3903

VARIABLE FILTER
997-11.50
II
Frequency in Hz
5 60

TS