997-11-50 **AGIP**

OFFSHORE ITALIA
ZONA F

SW 1 — LINEA F-75-59 — NE 609

1 km

COMPAGNIE GENERALE DE GEOPHYSIQUE

DIGITAL PROCESSING P5
TIME ORIGIN: Source and cable depth
STACK 4800 %
Boat motion →

550 | Date: MAY 14 76 | Checked RJ

**PROCESSING** SAMPLING RATE 4 ms

1 AMPLITUDE RECOVERY
2 WAPC (stabilization by vaporchoc signal)
3 MUTING
4 DECONVOLUTION 240 ms
window: 500 2300 ms ( Below
1900 3600 ms sea bottom
5 VELOCITY ANALYSIS (VA)
6 RMO CORRECTIONS
(LINEAR INTERPOLATION BETWEEN VELOCITY FUNCTIONS)
7 STACK 4800 %
8 TIME VARIANT FILTER (Origin sea bottom)
9 TRACE EQUALIZATION
10 ANALOG DISPLAY

**FIELD RECORDING** SAMPLING RATE 4 ms

Ship GLORITA TIDE Shooting date DEC (1975)
Field recorder SN 338 filter VB 125
Floating point sampling 4 ms
Streamer 2400 m (Depth 19 m)
groups 48 (group interval 50 m)
Geophones type HC 201 n° 48 / group
48 Fold coverage
Energy source VAPORCHOC (Depth 6 m)
SP 1rt Streamer Tr 48
310 m SHORAN positioning

00262

F-75.036
1230

Water depth in meters

NO SOUNDINGS

208 189 171 160

TWT

*FROM SP* TO SP * AV.VEL. IN M/S

| FROM SP | TO SP | AV.VEL. IN M/S |
|---|---|---|
| 1* | 12* | 1500 |
| 13* | 25* | 1530 |
| 257* | 384* | 1500 |
| 385* | 416* | 1500 |
| 417* | 575* | 1500 |
| 576* | 675 | 1518 |
| 2* | 12* | 1500 |
| 13* | 257* | 1530 |
| 258* | 384* | 1500 |
| 385* | 576* | 1522 |
| 577* | 675 | 1641 |

VARIABLE FILTER
997-11-50 IV
Frequency in Hz