997-11-50 **AGIP**

OFFSHORE ITALIA

ZONA F

SW 1210 — LINEA F-75-59 — NE 1809

1 km

COMPAGNIE GENERALE DE GEOPHYSIQUE

DIGITAL PROCESSING P5

TIME ORIGIN: Source and cable depth

STACK 4800 %

Boat motion →

552 | Date: MAY 14 .76 | Checked DM

PROCESSING SAMPLING RATE 4 ms

1. AMPLITUDE RECOVERY
2. WAPC (stabilization by vaporchoc signal)
3. MUTING
4. DECONVOLUTION 240 ms windows 500 - 2300 ms ↓ Below 1900 - 3600 ms ↑ sea bottom
5. VELOCITY ANALYSIS (VA)
6. NMO CORRECTIONS (LINEAR INTERPOLATION BETWEEN VELOCITY FUNCTIONS)
7. STACK 4800 %
8. TIME VARIANT FILTER (Origin sea bottom)
9. TRACE EQUALIZATION
10. ANALOG DISPLAY

FIELD RECORDING SAMPLING RATE 4 ms

Ship GLORITA TIDE Shooting date DEC /1975

Field recorder SN 338 filter √8.125

Floating point, sampling 4 ms

Streamer 2400 m (Depth 19 m) groups 48 (group interval 50 m)

Geophones type HC 201 n° 48 / group

48 Fold coverage

Energy source VAPORCHOC (Depth 6 m)

SP Trs Streamer Tr 48

310 m SHORAN positioning

00264

F 75.030 70

Water depth in meters

VA

CDP 1210 1220 1230 1240 1250 1260 1270 1280 1290 1300 1310 1320 1330 1340 1350 1360 1370 1380 1390 1400 1410 1420 1430 1440 1450 1460 1470 1480 1490 1500 1510 1520 1530 1540 1550 1560 1570 1580 1590 1600 1610 1620 1630 1640 1650 1660 1670 1680 1690 1700 1710 1720 1730 1740 1750 1760 1770 1780 1790 1800 1809

Fold 124 126 124 124 126 128 131 131 122 122 124 126 144 150 179 186 202 212 255 264 273

TWT 000 200 400 600 800 1000 1200 1400 1600 1800 2000 2200 2400 2600 2800 3000 3200 3400 3600 3800 4000 4200 4400 4600 4800 5000 5200 5400 5600 5800 6000

TWT	FROM SP * TO SP * AV. VEL. IN M/S	FROM SP * TO SP * AV. VEL. IN M/S	FROM SP * TO SP * AV. VEL. IN M/S	FROM SP * TO SP * AV. VEL. IN M/S	FROM SP * TO SP * AV. VEL. IN M/S	FROM SP * TO SP * AV. VEL. IN M/S
	925 * 925 *	1392 * 1392 *	1505 * 1505 *	1623 * 1623 *	1740 * 1740 *	1847 * 1847 *
000						
200	1500	1500	1502	1539	1500	1500
400	1655	1664	1664	1677	1550	1500
600	1781	1756	1746	1759	1687	1580
800	1981	1885	1847	1849	1755	1704
1000	2100	2052	1989	1923	1862	1819
1200	2300	2297	2217	2116	2066	1831
1400	2589	2515	2519	2278	2251	2235
1600	2693	2776	2648	2412	2410	2236
1800	3043	2981	2857	2669	2613	2469
2000	3253	3149	3171	2829	2842	2673
2200	3524	3463	3397	3104	3117	2814
2400	3761	3724	3644	3413	3482	3037
2600	3990	3946	3872	3658	3722	3293
2800	4183	4135	4067	3868	3928	3529
3000	4344	4299	4235	4050	4106	3734
3200	4485	4443	4383	4210	4262	3913
3400	4610	4570	4514	4350	4399	4071
3600	4720	4683	4629	4475	4521	4212
3800	4813	4784	4733	4587	4631	4337
4000	4908	4874	4826	4688	4729	4450
4200	4989	4957	4911	4779	4818	4553
4400	5062	5031	4988	4861	4899	4646
4600	5129	5099	5058	4937	4973	4731
4800	5190	5162	5122	5006	5041	4809
5000	5246	5219	5181	5070	5103	4880
5200	5299	5273	5236	5129	5161	4946
5400	5347	5322	5286	5183	5214	5008
5600	5391	5367	5332	5234	5264	5064
5800	5433	5410	5377	5281	5310	5117
6000	5472	5449	5417	5325	5353	5167

VARIABLE FILTER

997-11-50 IV

Frequency in Hz

0 5 10 15 20 25 30 40 50 60

T0 T1 T2 T3 T4 T5 T6