997-11-69 **AGIP**

OFFSHORE ITALIA

ZONA F

NW 1 — LINEA F-76-137 — SE 616

1 km

COMPAGNIE GENERALE DE GEOPHYSIQUE

DIGITAL PROCESSING P5

TIME ORIGIN: Source and cable depth

STACK 4800 %

Boat motion →

451 | Date: APRIL 9.76 | Checked

PROCESSING (SAMPLING RATE 4 ms)

1 AMPLITUDE RECOVERY
2 WAPE (stabilization by reference signal)
3 MUTING
4 DECONVOLUTION 240 ms
window 500 2300 ms } Below
1900 3600 ms } sea bottom
5 VELOCITY ANALYSIS (VA)
6 NMO CORRECTIONS
(LINEAR INTERPOLATION BETWEEN VELOCITY FUNCTIONS)
7 STACK 4800 %
8 TIME VARIANT FILTER (Origin sea bottom)
9 TRACE EQUALIZATION
10 ANALOG DISPLAY

FIELD RECORDING (SAMPLING RATE 4 ms)

Ship POLAR BJORN Shooting date: FEB/1976
Field recorder SN338B filter 1/8-125
floating point sampling 4 ms
Streamer 2400 m (Depth 15 m)
groups 48 (group interval 50 m)
Geophones type HC 201 n° 48 / group
48Fold coverage
Energy source VAPORCHOC (Depth 5 m)
SP n°1 Streamer n°48
230m MOTOROLA positioning

00357

F.76.074D 957

F.76.072D 390

VA

NO SOUNDINGS

Water depth in meters

TWT

1 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200 210 220 230 240 250 260 270 280 290 300 310 320 330 340 350 360 370 380 390 400 410 420 430 440 450 460 470 480 490 500 510 520 530 540 550 560 570 580 590 600 616

000 200 400 600 800 1000 1200 1400 1600 1800 2000 2200 2400 2600 2800 3000 3200 3400 3600 3800 4000 4200 4400 4600 4800 5000 5200 5400 5600 5800 6000 6200 6400

TWT	*FROM SP* 1 * TO SP * AV.VEL * IN M/S*	*FROM SP* 107* TO SP * AV.VEL * IN M/S*	*FROM SP* 214* TO SP * AV.VEL * IN M/S*	*FROM SP* 321* TO SP * AV.VEL * IN M/S*	*FROM SP* 428* TO SP * AV.VEL * IN M/S*	*FROM SP* 535* TO SP * AV.VEL * IN M/S*
000						
200	1500	1500	1500	1500	1500	1500
400	1500	1500	1500	1500	1500	1500
600	1729	1550	1500	1500	1500	1500
800	1797	1642	1560	1500	1500	1500
1000	1982	1806	1660	1560	1500	1500
1200	2177	1992	1826	1693	1588	1500
1400	2316	2142	1972	1844	1708	1600
1600	2498	2319	2150	1992	1837	1715
1800	2640	2464	2292	2127	1977	1822
2000	2799	2599	2403	2261	2113	1967
2200	2971	2762	2527	2326	2185	2035
2400	3124	2949	2732	2509	2328	2159
2600	3236	2713	2480	2301	2064	1998
2800	3409	2940	2642	2440	2230	2057
3000	3566	3137	2854	2650	2449	2274
3200	3708	3304	3038	2854	2654	2491
3400	3831	3451	3208	3028	2839	2686
3600	3940	3581	3345	3162	3004	2859
3800	4038	3696	3474	3319	3151	3013
4000	4126	3803	3590	3443	3283	3153
4200	4206	3895	3699	3550	3403	3279
4400	4278	3984	3791	3650	3512	3393
4600	4344	4063	3870	3751	3611	3496
4800	4405	4136	3950	3830	3703	3594
5000	4461	4202	4030	3919	3786	3682
5200	4512	4264	4100	3987	3864	3763
5400	4560	4321	4163	4054	3936	3839
5600	4604	4373	4221	4117	4002	3909
5800	4645	4423	4279	4175	4064	3974
6000	4684	4468	4327	4229	4122	4035
6200	4720	4511	4374	4279	4176	4092
6400	4754	4552	4419	4327	4227	4145

VARIABLE FILTER
997 11 69
VI
Frequency in Hz
11 55
9 35