997-11-69 **AGIP**

OFFSHORE ITALIA

ZONA F

SW 1180 **LINEA F-76-74E** NE 551

1 km

COMPAGNIE GENERALE DE GEOPHYSIQUE

DIGITAL PROCESSING P5

TIME ORIGIN: Source and cable depth

STACK 4800 %

Boat motion

536 | Date: MAY 12 .76 | Checked

PROCESSING SAMPLING RATE 4 ms

1 AMPLITUDE RECOVERY
2 WAPC (stabilization by vaporchoc signal)
3 MUTING
4 DECONVOLUTION 240 ms
windows: 500 2300 ms } Below
1900 3600 ms } sea bottom
5 VELOCITY ANALYSIS (VA)
6 NMO CORRECTIONS
(LINEAR INTERPOLATION BETWEEN VELOCITY FUNCTIONS)
7 STACK 4800 %
8 TIME VARIANT FILTER (Origin sea bottom)
9 TRACE EQUALIZATION
10 ANALOG DISPLAY

FIELD RECORDING SAMPLING RATE 4 ms

Ship: POLAR BJORN Shooting date: FEB/1976
Field recorder: SN338B filter: 1/8-125
floating point sampling: 4 ms
Streamer: 2400 m (Depth: 15 m)
groups: 48 (group interval: 50 m)
Geophones type: HC 201 n° 48 / group
48Fold coverage
Energy source: VAPORCHOC (Depth: 5 m)
SP 1 to 1 Streamer 1 to 48
330M MOTOROLA positioning

00322

F-76-131
30

Water depth in meters: 390 196 194 152 220 176 158 374 628 402 420 264 233 248

VA

TWT 1180 1160 1150 1140 1130 1120 1110 1100 1090 1080 1070 1060 1050 1040 1030 1020 1010 1000 990 980 970 960 950 940 930 920 910 900 890 880 870 860 850 840 830 820 810 800 790 780 770 760 750 740 730 720 710 700 690 680 670 660 650 640 630 620 610 600 590 580 570 560 551

000 200 400 600 800 1000 1200 1400 1600 1800 2000 2200 2400 2600 2800 3000 3200 3400 3600 3800 4000 4200 4400 4600 4800 5000 5200 5400 5600 5800

FROM SP *FROM SP* *FROM SP* *FROM SP* *FROM SP* *FROM SP* *FROM SP*
* 1199* 1080* 959* 837* 727* 673* 477*
* TO SP * TO SP * TO SP * TO SP * TO SP * TO SP * TO SP *
* 1200* 1125* 960* 839* 728* 655* 479*

TWT *AV.VEL.* *AV.VEL.* *AV.VEL.* *AV.VEL.* *AV.VEL.* *AV.VEL.* *AV.VEL.*
* IN M/S* IN M/S* IN M/S* IN M/S* IN M/S* IN M/S* IN M/S*

000	*	*	*	*	*	*	*
200	1500	1500	1500	1505	1500	1500	1500
400	1500	1503	1503	1774	1530	1543	1551
600	1584	1588	1659	1639	1530	1545	1563
800	1626	1792	1777	1782	1590	1766	1774
1000	1734	1920	1949	1914	1612	1892	1892
1200	1876	2076	2130	2061	1706	2093	2026
1400	1977	2218	2291	2204	1836	2242	2144
1600	2156	2417	2439	2295	1947	2377	2274
1800	2417	2591	2587	2453	2057	2505	2381
2000	2634	2745	2736	2576	2200	2632	2493
2200	2865	2881	2891	2761	2285	2793	2626
2400	2992	2996	3051	3010	2488	2988	2821
2600	3190	3118	3187	3203	2701	2999	2947
2800	3360	3304	3379	3317	2956	3241	3110
3000	3532	3483	3554	3399	3199	3438	3269
3200	3687	3641	3707	3562	3375	3598	3448
3400	3823	3779	3842	3705	3529	3739	3591
3600	3944	3903	3962	3837	3666	3865	3724
3800	4052	4013	4069	3947	3781	3977	3844
4000	4149	4112	4165	4049	3883	4078	3952
4200	4237	4202	4253	4142	4000	4170	4049
4400	4317	4284	4332	4227	4090	4253	4138
4600	4390	4359	4405	4304	4173	4329	4219
4800	4458	4427	4471	4374	4250	4398	4293
5000	4519	4490	4532	4439	4319	4463	4361
5200	4576	4548	4589	4499	4384	4523	4424
5400	4629	4602	4641	4555	4444	4578	4483
5600	4678	4652	4689	4607	4503	4627	4537
5800	4723	4698	4735	4655	4551	4674	4587

VARIABLE FILTER
997 11 69
VI
Frequency in Hz
11 55