A 1085

LINE FR-309-80

S.P. 106 TO S.P. 446



1000 PCT DBS-TVF

SP 106.00	
TIME	MIG.VEL.
0.10	2400
0.45	3400
1.10	3900
1.70	4200
2.00	4400
6.50	5400

SP 446.00	
TIME	MIG.VEL.
0.10	2400
0.45	3400
1.10	3900
1.70	4200
2.00	4400
2.50	5400

SP 106 V

SP 446 V

LINE FR-309-80

ELEV. 106 118 130 142 154 166 178 190 202 214 226 238 250 262 274 286 298 310 322 334 346 358 370 382 394 406 418 430 442 DATUM CORR.

400 M. 200 M. 0 M. -300 MS -150 MS 0 MS

0 1 KM

AGIP

WESTERN

RICERCHE GEOFISICHE

ITALIA-ZONA 4
PROSPECT CECCANO-ALATRI

DATE SHOT MAY 1981

RECORDING DATA

PARTY NUMBER	R.I.G. SRL IT.16
RECORDER	DFS IV
CREW	WTP
RECORDING FILTER LC,(HZ)	12/180B
ALIASING FILTER (HZ)	124/72DB
RECRD LENGTH (SEC)	7
SAMPLE RATE	2
SUBSURFACE COVERAGE	1000PCT
GROUP INTERVAL (METERS)	60
NUMBER OF TRACES/S.P.	60
WEATHERING VELOCITY	350 M/S
SUBWEATHERING VELOCITY	2500 M/S
DATUM PLANE	SEA LEVEL

SPREAD DIMENSIONS

1 60 61 120
20M 20M
1180M 1180M

CENTRE OF SOURCE ARRAY
DIRECTION OF LINE N-S

SEISMOMETER ARRAY

GEOPHONE TYPE	SM4
GEOPHONE FREQUENCY	10 HZ
GEOPHONE/GROUP	36

X = 40 M

S.P. PATTERN

ENERGY SOURCE	DINAMITE
SHOT HOLES/S.P.	1
AVERAGE CHARGE/SHOT	6 KG
AVERAGE SHOT DEPTH	36 M

PROCESSING SEQUENCE

EDIT GEO,AMPL, SR 2MS LEN,7.0 SEC

TIME VARIANT PREFILTER

RMS GAIN

PREPROCESSOR/DECON

DECON TYPE MINIMUM PHASE INVERSE FILTER
MIN. PRED. DIST 2MS. MAX. PRED. DIST. 180MS
NO.OF WINDOWS 1
REEL NO. 104744 SL

CONSTANT VELOCITY STACK

17 VELOCITY FUNCTIONS

SURFACE CONSISTENT RESID. STATICS

NMO, STATICS, MUTE APPLICATION

STRETCHING DEPENDENT MUTE

CDP CONSISTENT RESIDUAL STATICS

STA

REEL NO. 102814 SL

TIME VARIANT BANDPASS FILTER

TIME	LC.	HC.
0.0	10	70
0.1	10	70
0.8	14	65
2.0	12	38
6.0	10	36

RMS GAIN

LEGEND

V VELOCITY ANALYSIS

INTERSECTIONS

ANALYST [signature] DATE 21.7.81

LINE LOCATION MAP