
Y4851000
X1601000
X1602000
X1603000
X1604000
X1605000
Y4851000
X1606000
X1607000
X1608000
Y4852000
X1609000
X1610000
X1611000
Y4853000
X1611000
X1601000
Y4852000
X1602000
X1603000
Y4853000
X1605000
X1606000
Y4854000
X1608000
X1609000
X1610000
GP 438
626
576
526
476
426
376
326
276
226
176
126
76
26
GP 101
Geophone Line
CDP
LINE PIC-03-89V


ELEVATION
DATUM PLANE
GEOPHONE CORRECTION
PIC-01-89V / SP236
PIC-02-89V / SP157
STATIONS
COVERAGE
CDP 6200DC -28
CDP 5900DC -28
CDP 5600DC -29
CDP 4600DC +30
CDP 4400DC -29
CDP 3400DC +27
CDP 2800DC -26
CDP 2200DC -27
CDP 1600DC -27
CDP 1000DC -26
CDP 10C -26
CDP 40DC +26
PIC-01-89V / CDP 265
PIC-02-89V / CDP 11E
C.D.P.


CGG - DATA PROCESSING SERVICES
1 RUE LEON BLOUDIN 91341 MASSY CEDEX FRANCE
CANADA NORTHWEST
VIAREGGIO
PIC-03-89V
SW 437
101 NE
VIBRATED POINT
STACK TVF
RANDOM NOISE ATTENUATION
80 FOLD COVERAGE
SLALOM LINE *
* CGG TRADE MARK
107 95 74CC *
PL 1 SAR
* CGG PROJECT NUMBER
DATE : SEPT 1989
FIELD RECORDING
CONTRACTOR CGG
DATE MAY 04-MAY 08 1989
RECORDER JB 368
TAPE 6250 BPI SG-141-145
FORMAT SEG-D
COVERAGE 80
SAMPLING RATE 2 MS
RECORDING LENGTH 4000 MS
FILTERS
LC 8 HZ (18DB/OCT)
HC 178 HZ (18DB/OCT)
SHOT-GEOPHONE ARRAY-SPREAD
** SOURCE **
VIBRATORS
TYPE MERTZ 18
SPACING 25 M
POLARITY ALTERNED
ELECTRONIC CONTROL SRV 310 A
SWEEP / FREQUENCY 10 - 70 HZ
LENGTH 12 S
NUMBER OF LOCATION / VP 4
NUMBER OF SWEEP / LOCATION 1
LOCATION SPACING 6.25
** RECEPTION **
GEOPHONE TYPE GSC 20 D
FREQUENCY 10 HZ
GEOPHONE PER GROUP 10
NUMBER OF TRACES 120
TRACE SPACING 25 M
GEOPHONE SPACING 1.5M
** SPREAD **
SURFACE CORRECTIONS
METHOD SPHOLE VT
DATUM PLANE (DP)= 0 M
REVISER TO DP VELOCITY 2000 M/S
CORRECTION SIGN + SHORTENS TIMES
PROCESSING : CGG
SIGNAL LENGTH PROCESSED : 4 S
SAMPLING INTERVAL : 4 MS
DEMULTIPLEXING AND RESAMPLING
TRACE EDITING
AMPLITUDE RECOVERY
REFLECTION POINT GATHERING
ZERO PHASE DECONVOLUTION
FILTERING :
13-54 HZ T 0 - 800 MS
15-65 HZ T 2400 - 3600 MS
15-40 HZ T 4000 MS
TRACE EQUALIZATION * 600 MS
STATIC CORRECTIONS (FROM GROUND LEVEL TO DPC +
ASTRONOMIC STATICS ;
MEDIUM WAVE LENGTH SURFACE CONSISTENT STATICS
DATAN IV MF 3
VELOCITY ANALYSIS (ANVIT VELSUM)
NMO CORRECTIONS LINEAR INTERPOLATION BETWEEN VELOCITY FUNCTIONS
STATIC CORRECTIONS (FROM DPC+ TO DP)
AUTOMATIC STATICS :
SURFACE CONSISTENT STATICS/DATAN I
STACK 4000 B/O FOLD
RANDOM NOISE ATTENUATION
BAND PASS FILTER : 18 - 60 HZ
TRACE EQUALIZATION :
L = 300 MS T = 0 : 1800 MS
L = 600 MS T =1800 : 4000 MS
ANALOG DISPLAY
* DPC : THE AVERAGE GROUND LEVEL ELEVATION IS REPRESENTED BY A BLACK PEAK AT THE TOP OF THE SECTION.
POLARITY CONVENTION
COMPRESSION=NEGATIVE VALUE ON TAPE
AFTER PROCESSING=WHITE TROUGH OR SECTION


SCALE
80 TR. = 1 KILOMETER
2°10'W
LUC-01
LUC-02
PIC-04
PIC-02
PIC-03
PIC-05
PIC-04
N
CANADA N.W.
VIAREGGIO
ITALY
127-35-74CC
1 KM
4860
4850
43°50'N
1600
1610