



SERGONE IDROCARBURI
PER USO ESCLUSIVO

CGG - DATA PROCESSING SERVICES
1 RUE LEON BLOUIN 91341 MASSY CEDEX FRANCE

CANADA NORTHWEST

VIAREGGIO

PIC-05-89V

SW 444 — 101 NE

VIBRATED POINT

STACK TVF
RANDOM NOISE ATTENUATION
60 FOLD COVERAGE
SLALOM LINE *
* CGG TRADE MARK

127 35 74CC * — PL : 78R
* CGG PROJECT NUMBER — DATE : SEPT 1989

FIELD RECORDING

CONTRACTOR	CGG	SAMPLING RATE	2 MS
DATE	SAT 13-SAT 13 1989	RECORDING LENGTH	4000 MS
RECORDER	SN 368	FILTERS :	
TAPE	6250 BPI	NO.1511145	LC 8 HZ (18DB/OCT)
FORMAT		SEG-D	HC 176 HZ (18DB/OCT)
COVERAGE		60	

SHOT-GEOPHONE ARRAY-SPREAD

•• SOURCE ••

TYPE	VIBRATORS		
NUMBER	2	SWEEP : FREQUENCY	10 - 70 HZ
SPACING	20 M	LENGTH	10 S
POLARITY	ALTERNED	NUMBER OF LOCATION / VP	4
ELECTRONIC CONTROL	SSV 310 A	NUMBER OF SWEEP / LOCATION	1
		LOCATION SPACING	6.25

•• RECEPTION ••

GEOPHONE TYPE	GSC 20 D	NUMBER OF TRACES	120
FREQUENCY	10 HZ	TRACE SPACING	25 M
GEOPHONE PER GROUP	12	GEOPHONE SPACING	1.56

•• SPREAD ••

SURFACE CORRECTIONS

METHOD:	SPROLE VT	DATUM PLANE (DP):	0 M
RETURN TO DP VELOCITY:	2000 M/S	CORRECTION SIGN:	+ SHORTENS TIMES

PROCESSING : CGG

SIGNAL LENGTH PROCESSED : 4 S	SAMPLING INTERVAL : 4 MS
DEMULTIPLEXING AND RESAMPLING	DATAN IV NF 3
TRACE EDITING	VELOCITY ANALYSIS (ARVITE VELOCITY)
AMPLITUDE RECOVERY	RMO CORRECTIONS LINEAR INTERPOLATION
REFLECTION POINT GATHERING	BETWEEN VELOCITY FUNCTIONS
ZERO PHASE DECONVOLUTION	STATIC CORRECTIONS (FROM DPC• TO DP)
. FILTERING :	AUTOMATIC STATICS :
. 13-64 HZ T 0 - 800 MS	SURFACE CONSISTENT STATICS-DATAN I
. 10-55 HZ T 2400 - 3600 MS	STACK 6000 6-01 FOLD
. 11-40 HZ T 4000 MS	RANDOM NOISE ATTENUATION
TRACE EQUALIZATION : 400 MS	RAND PASS FILTER : 18 - 60 HZ
STATIC CORRECTIONS (FROM GROND LEVEL TO DPC •) :	TRACE EQUALIZATION : . L = 300 MS T = 0 - 1600 MS . L = 600 MS T =1800 - 4000 MS
AUTOMATIC STATICS : RESIDE WAVE LENGTH SURFACE CONSISTENT STATICS	ANALOG DISPLAY

• DPC : THE AVERAGE GROUND LEVEL ELEVATION IS REPRESENTED BY A BLACK PEAK AT THE TOP OF THE SECTION.

POLARITY CONVENTION

COMPRESSION=NEGATIVE VALUE ON TAPE
AFTER PROCESSING=WHITE TROUGH OF SECTION

SCALE
80 TR. = 1 KILOMETER