



SL 4
OUT
2 20 0
1092

REQ N°	L-39/B
Section N°	1042-C
System Code	MSTV
Assembled by	
Checked by	

AGIP
ADRIATIC SEA ZONE B
LINE B 429 (TVF)
1967 GEOPHYSICAL SERVICE INTERNATIONAL LTD

SHOOTING PARAMETERS	
12 Fold Off End	
Shot by G.S.I. PTY 903	
Cable Length 2430 m	
Group Interval 100 m	
Shot Point Interval 100 m	
Average Shot Offset 100 m	
Charge Size 50 lb	
Average Sea Depth 12 m	

RECORDING PARAMETERS	
System 9000	
Record Length 5.0	
Sample 2ms	
AGC Trip 78dB (Pre 80dB)	
Filters Hi 75cps (36db/oct)	
Lo 8cps (24db/oct)	
2ms Anti Alias Filtering	

SEIS EDIT & NMO	
TAR	
From 0 sec to 4.0 sec	
Water Velocity 1522 m/sec	
Replacement Vel 1522 m/sec	

DECONVOLUTION	
Time Variant ARD	
Filter Length 2.00 sec	
Gate Length 2.2 sec	
Initial Gates Trace 2	
Final Break Suppression	
T1 0.6 sec T2 1.2 sec	
T3 1.5 sec T4 2.4 sec	
T5 4.0 sec T6 24.3 sec	

6-FOLD STACK	
Optimum Wide Band Stack	
RRMO Ws Diversity Stack Yes	
First Break Suppression	
T1 0.6 sec T2 1.2 sec	
T3 1.5 sec T4 2.4 sec	
T5 4.0 sec T6 24.3 sec	



DISPL 47
Avg. Time 1092
118 12 14 16

REQ N°	L-3901
Section N°	1041-C
System Code	MSTV
Assembled by	
Checked by	

AGIP
ADRIATIC SEA ZONE B
LINE B 429 (TVF)
1967 GEOPHYSICAL SERVICE INTERNATIONAL LTD

SHOOTING PARAMETERS	
6 Fold Off End	
Shot by G.S.I. PTY 903	
Cable Length 1600 m	
Group Interval 67 m	
Shot Point Interval 134 m	
Average Shot Offset 160 m	
Charge Size 50 lb	
Average Sea Depth 12 m	

RECORDING PARAMETERS	
System 9000	
Record Length 5.0	
Sample 2ms	
AGC Trip 78dB (Pre 80dB)	
Filters Hi 75cps (36db/oct)	
Lo 8cps (24db/oct)	
2ms Anti Alias Filtering	

SEIS EDIT & NMO	
TAR	
From 0 sec to 4.0 sec	
Water Velocity 1522 m/sec	
Replacement Vel 1522 m/sec	

DECONVOLUTION	
Time Variant ARD	
Filter Length 2.00 sec	
Gate Length 2.2 sec	
Initial Gates Trace 1	
Final Break Suppression	
T1 0.6 sec T2 1.2 sec	
T3 1.5 sec T4 2.4 sec	
T5 4.0 sec T6 24.3 sec	

6-FOLD STACK	
Optimum Wide Band Stack	
RRMO Ws Diversity Stack Yes	
First Break Suppression	
T1 0.6 sec T2 1.2 sec	
T3 1.5 sec T4 2.4 sec	
T5 4.0 sec T6 24.3 sec	

LINE B 442 SP 2028 390 370 350 330 310 290 280 270 260 250 240 230 220 210 200 190 180 170 160 150

