

MTI
LINE 40
SP I-145
24 FOLD CDPSUM

1 KILOMETER

SOUTHEAST

AREA DR-40 (ADRIATIC SEA) MINERARIA TEXAS ITALIAN
LINE NO. 40 SP's I-145

PROCESSING FIELD DATA

EXPONENTIAL GAIN RATE 4db/Sec GATE 0-3.0 Sec
 VERTICAL STACK TWO ON ONE
 NORMAL MOVEOUT
 TV DECON MULTICHANNEL DECON
SP I-145 NO FILTERS 5 WHITE NOISE 1%
FILTER LENGTH 100 ms
DESIGN GATES NEAR OFFSET 100-100, 800-1800,
1,600-2,600, 2,400-3,400, 3,300-4,300, 4,000-4,900 Sec.
DESIGN GATES FAR OFFSET 100-1100, 800-1800,
1,600-2,600, 2,400-3,400, 3,300-4,300, 4,000-4,900 Sec.
SP NO. FILTERS WHITE NOISE
FILTER LENGTH ms
DESIGN GATES NEAR OFFSET
DESIGN GATES FAR OFFSET

VELOCITY ANALYSIS
 RESIDUAL NORMAL MOVEOUT
 COMMON DEPTH POINT GATHER
 COMMON DEPTH POINT SUM 24 FOLD
 DIGITAL FILTER NO FILTERS 3
BAND PASS 15-45 cps TIME 0-.500 sec
10-40 cps 1100 sec.
10-25 cps 2100-5,000 sec.

TRACE AMPLITUDE EQUALIZATION
 SINGLEFOLD DISPLAY
 VELOCITY ANALYSIS

RECORDING INST. T1 11,000, DFS III, 48 TRACE
RECORDING FILTERS 8-62 cps
SPREAD CONFIGURATION - END ON 585'-8293' OFFSET
GAIN INFORMATION - BINARY GAIN
ARRAY - 19 GUNS
2 - 80 IN³ (2-40) 6 - 20 IN³
6 - 40 IN³ 5 - 10 IN³

RECORDED AND PROCESSED BY
digicon inc.
HOUSTON, TEXAS

MTI
LINE 40
SP I-145
24 FOLD CDPSUM

