

LINE 6
 SP 309-102
 2 x 24 FOLD STACK



1 KILOMETER

AREA TYRRHENIAN SEA SOCIET ITALIANA RESINE
 LINE NO 6 SP's 309-102
 FIELD DATA

1 EXPONENTIAL GAIN RATE 4db/Sec. RATE 0-3.0 Sec.	4 VELOCITY ANALYSIS	RECORDING INST. 11 11000 0FS 11 48 TRACE
2 VERTICAL STACK TWO ON ONE	5 PRECIPITAL NORMAL MOVEOUT	RECORDING FILTERS 8-63
3 NORMAL MOVEOUT	6 COMMON DEPTH POINT GATHER	SPREAD CONFIGURATION END ON 255-7965 OFFSET
7 309-102 NO FILTERS 1 WHITE NOISE 1%	7 SERIAL FILTERS NO FILTERS 3	DATA REPRESENTATION BINARY GAIN
FILTER LENGTH 400 ms	8 BAND PASS 15-45 cps TIME 0	ARRAY 21 GUNDS
DESIGN GATES NEAR OFFSET 0-4.500 Sec.	9-10 40-125 AT MAJOR UNCONFORMITY	2-80 IN ² (2-80) 6 20 IN ²
DESIGN GATES FAR OFFSET 0-4.500 Sec.	10-30-655	5-40 IN ² 7-10 IN ²
SP NO FILTERS WHITE NOISE	9 TRACE AMPLITUDE EQUALIZATION	RECORDED AND PROCESSED BY
FILTER LENGTH ms	10 SINGLEFOLD DISPLAY	
DESIGN GATES NEAR OFFSET	11 VELOCITY ANALYSIS	
DESIGN GATES FAR OFFSET		

digicon inc.
 HOUSTON, TEXAS

