

LINE 9
 SP 101-229
 2 x 24 FOLD STACK

SOUTHEAST

1 KILOMETER

AREA TYRRHENIAN SEA

SOCIETA ITALIANA RESINE
 LINE NO. 9

SP's 101-230

PROCESSING

1 EXPONENTIAL GAIN RATE 4db/Sec. GATE 0-3.0 Sec.
 2 VERTICAL STACK TWC ON ONE
 3 NORMAL MOVEOUT
 7 TV DECON MULTICHANNEL DECON
 SP 101-230 NO FILTERS 3 WHITE NOISE 1%
 FILTER LENGTH 176 ms
 DESIGN GATES NEAR OFFSET .050-1.800,
 1.500-3.300, 3.000-4.800 Sec.
 DESIGN GATES FAR OFFSET .050-1.800,
 1.500-3.300, 3.000-4.800 Sec.
 SP NO FILTERS WHITE NOISE
 FILTER LENGTH ms
 DESIGN GATES NEAR OFFSET
 DESIGN GATES FAR OFFSET

4 VELOCITY ANALYSIS
 RESIDUAL NORMAL MOVEOUT
 5 COMMON DEPTH POINT GATHER
 6 COMMON DEPTH POINT SUM 24 FOLD
 8 DIGITAL FILTER NO FILTERS 3
 BAND PASS 15-45 cps TIME 0
 10-40 cps AT MAJOR UNIFORMITY
 10-30 cps 2.500 5.000
 9 TRACE AMPLITUDE EQUALIZATION
 SINGLEFOLD DISPLAY
 VELOCITY ANALYSIS

FIELD DATA

RECORDING INSTR. T 11,000 L DPS III 48 TRACE
 RECORDING FILTERS B-62 cps
 SPREAD CONFIGURATION "END ON 255-7963" OFFSET
 GAIN INFORMATION BINARY GAIN
 ARRAY - 21 GUNS
 2-80 IN (2-40) 6-20 IN
 6-40 IN 7-10 IN

RECORDED AND PROCESSED BY

