

LINE 13
 SP 110-240
 24 FOLD STACK

1 KILOMETER

NORTHEAST

AREA TYRRHENIAN SEA SOCIETA ITALIANA RESINE LINE NO 13 SP'S 110-240

1 EXPONENTIAL GAIN RATE 4db/Sec. GATE 0-3.0 Sec.
 NORMAL STACK TWC OR ONE
 4 NORMAL MOVEOUT
 6 MONO MULTICHANNEL DECON
 110-241 NO FILTERS 4 WHITE NOISE 1%
 FILTER LENGTH 120 ms
 DESIGN GATES NEAR OFFSET 100 - 1.300,
 1.000 - 2.400, 2.100 - 3.500, 3.200 - 4.700 Sec.
 DESIGN GATES FAR OFFSET 100 - 1.300,
 1.000 - 2.400, 2.100 - 3.500, 3.200 - 4.700 Sec.
 SP NO FILTERS WHITE NOISE
 FILTER LENGTH ms
 DESIGN GATES NEAR OFFSET
 DESIGN GATES FAR OFFSET

3 VELOCITY ANALYSIS
 RESIDUAL NORMAL MOVEOUT
 2 COMMON DEPTH POINT GATHER
 5 COMMON DEPTH POINT SHIM 2.4 FOLD
 7 DIGITAL FILTER NO FILTERS 3
 BAND PASS 15 - 45 cps TIME 0
 12 - 40 cps 1.500 sec
 10 - 35 cps 2.500 - 5.000 sec

8 TRACE AMPLITUDE EQUALIZATION
 SINGLEFOLE DISPLAY
 VELOCITY ANALYSIS

RECORDING INSTRUMENT HOUSTON, TEXAS
 RECORDING FILTERS 8-62 cps
 SPECIAL CONFIGURATION - END ON 585-4357' OFFSET
 MAIN INFORMATION - BINARY GAIN
 ARRAY 21 GUNS
 2-60 IN² 12-40 6-20 IN²
 6-42 IN² 7-10 IN²

FIELD DATA
 RECORDED AND PROCESSED BY


