



RECORDING DATA	
PARTY No	62
ENERGY SOURCE	AQUAPULSE
FILTER	HI/62 - LO/8
CABLE	48 GROUPS - 2400 m.
GEOPHONES	20 CRYSTAL ELEMENT
EVENLY SPACED	1.52 m. APART
LEAD IN	285 m.
AMPLIFIER	S.D.S. BINARY GAIN
CHARGE SIZE	4 GUN POPS
GUN DEPTH	9.0 m.
AVG. CABLE DEPTH	9.0 m.
DATE SHOT	DEC. 1972

PROCESSING INFORMATION																													
SAMPLE RATE 4 ms																													
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: center;">DECON BEFORE STACK</th> </tr> </thead> <tbody> <tr> <td colspan="2">TIME VAR. MIN. PHASE INVERSE FILTER</td> </tr> <tr> <td colspan="2">AUTO CORR. INT.: 2 ZONES</td> </tr> <tr> <td colspan="2">SEARCH ZONE: 32 ms. TO 200 ms.</td> </tr> <tr> <td colspan="2">OPERATOR LENGTH: SEARCH ZONE</td> </tr> <tr> <td colspan="2">TIME ZONE: 0 - 5.0 SEC</td> </tr> <tr> <td colspan="2">ITERATIONS: 1</td> </tr> </tbody> </table>	DECON BEFORE STACK		TIME VAR. MIN. PHASE INVERSE FILTER		AUTO CORR. INT.: 2 ZONES		SEARCH ZONE: 32 ms. TO 200 ms.		OPERATOR LENGTH: SEARCH ZONE		TIME ZONE: 0 - 5.0 SEC		ITERATIONS: 1		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: center;">TIME VARIANT FILTER</th> </tr> <tr> <td></td> <td style="text-align: center;">L.C. H.C.</td> </tr> <tr> <td style="text-align: center;">TIME ZONE Hz dB/OCT</td> <td style="text-align: center;">Hz dB/OCT</td> </tr> </thead> <tbody> <tr> <td style="text-align: center;">VARIABLE</td> <td style="text-align: center;">15 18 50 48</td> </tr> <tr> <td style="text-align: center;">"</td> <td style="text-align: center;">10 12 45 48</td> </tr> <tr> <td style="text-align: center;">"</td> <td style="text-align: center;">8 12 35 48</td> </tr> <tr> <td style="text-align: center;">"</td> <td style="text-align: center;">7 12 30 48</td> </tr> </tbody> </table>	TIME VARIANT FILTER			L.C. H.C.	TIME ZONE Hz dB/OCT	Hz dB/OCT	VARIABLE	15 18 50 48	"	10 12 45 48	"	8 12 35 48	"	7 12 30 48
DECON BEFORE STACK																													
TIME VAR. MIN. PHASE INVERSE FILTER																													
AUTO CORR. INT.: 2 ZONES																													
SEARCH ZONE: 32 ms. TO 200 ms.																													
OPERATOR LENGTH: SEARCH ZONE																													
TIME ZONE: 0 - 5.0 SEC																													
ITERATIONS: 1																													
TIME VARIANT FILTER																													
	L.C. H.C.																												
TIME ZONE Hz dB/OCT	Hz dB/OCT																												
VARIABLE	15 18 50 48																												
"	10 12 45 48																												
"	8 12 35 48																												
"	7 12 30 48																												

PROCESSING SEQUENCE
1) EDIT (SUM I POP)
2) DECONVOLUTION BEFORE STK
3) 4800 % STK
4) MULTI-CHANNEL FILTER NONE
5) TV FILTER
6) PLAYBACK
VELOCITIES INTERPOLATED BETWEEN POINTS OF APPLICATION
CORRECTION TO SEA LEVEL = 0
REEL No 88319
DATE FEB. 1973

LEGEND
INTERSECTION:
VELOCITY APPLIED:
VELOCITY ANALYSIS:
SHOT POINT No.: 100
WATER DEPTH IN METRES: 10

LINE DR-545F
 S.P. 1 to S.P. 25
 DATUM PLANE : SEA LEVEL

