
INSTRUMENTS
AMPLIFIER
FILTER
RECORD LENGTH
SAMPLE RATE
RECORDING TAPE
TYPE AMPLITUDE CONTROL
RECORDING FORMAT
DFS IV
8/18-62/72Hz
5 sec
4 ms
FLOATING POINT
1/2" 1600 BPI
SEG C
POLARITY CONVENTION COMPRESSIONAL WAVE RECORDED AS A NEGATIVE
NUMBER AND DEFLAXED AS A TROUGH (WHITE)
SOURCE
BOAT
M/V LONGVA I
NAVIGATION
MAP LOCATION
AIRGUNS
CHARGE SIZE
GUN DEPTH
SP INTERVAL
SAT. NAV
REFL. POINT
4378 cu in
7m
25m
CABLE
2400m
GEOPHONES PER GROUP
GROUPS
GROUP INTERVAL
CABLE DEPTH
30
48
50m
12-15 m
RECORDING DATA
SHOT BY
PROCESSED BY
CONTRACT NO.
GECO A/S
GECO A/S
835
DATE: FEB. 1977
DATE: MARCH 1977
STACK REEL NO 59596
A
B
C
D
E
F
G
37°15'N
37°20'N
12°15'E
12°20'E
LINE C
SP 1 to SP 454
2×2400% FILTERED STACK
NE
BOMIN OIL
AREA: SICILY
PROCESSING SEQUENCE AND PARAMETERS
EDIT/DEMULTIPLEX SUMMATION OF TWO ADJ. SHOTS
DBS
PRE PROCESSING DPP GAINER
CORRECTIONS FOR SPHERICAL DIVERGENCE
TYPE MINIMUM PHASE INVERSE FILTER
MINIMUM PREDICTION DISTANCE 32 ms
MAXIMUM PREDICTION DISTANCE 160 ms
LENGTH OF OPERATOR 128 ms
NMO/STACK
DAS
STOP OF DECONVOLUTION 5000 ms
NO OF AUTOCORR WINDOWS 2
STOP OF AUTOCORR 5000 ms
TYPE MINIMUM PHASE INVERSE FILTER
MINIMUM PREDICTION DISTANCE 28 ms
MAXIMUM PREDICTION DISTANCE 150 ms
START OF AUTOCORR 100ms
NO OF AUTOCORR WINDOWS 1
STOP OF AUTOCORR 5000ms
STOP OF DECONVOLUTION 5000ms
TV FILTER Sec LC HC Slopes dB/Oct
0.0 - 0.5 8 - 50 18/2
0.2 - 1.55 8 - 45 18/2
2.0 - 3.6 8 - 35 18/2
0.85 - 2.7 8 - 0.50 18/2
4.0 - 5.0 8 - 30 18/2
STATICS SHOT AND RECEIVER COMP 13 ms
1/1 SCALE
PLAYBACK SCALES HORIZONTAL 5 in/cm
VERTICAL 10cm/sec
GAIN 9 dB
BIAS -4 %
HORIZONTAL SCALE 1: 12 500
0 250 500 m
20 SP's
LEGEND | = INTERSECTION V = VELOCITY ANALYSIS
WD = WATER DEPTH IN METERS
SEZIONE IDROGRAFICA
20 OTT. 1977
3451