

SICILY GROUP - AMOCO
LINE ZC-216
SP 820-625

SOUTHEAST

LINE ZC-216

SHOTPOINTS 820-625

PROJECT SICILY GROUP - AMOCO

FIELD DATA

RECORDING SYSTEM 11 DFS III
DATA STORAGE BINARY
RECORDING RATE 18.62 Hz
TRAIL HEAD 4 MS
SPACING 50 METERS
RECORDING TIME 48
MARKER INTERVAL 200.8 METERS
MARKER TOLERANCE 100 METERS
MARKER STRENGTH
MARKER QUALITY AIRGUNS
MARKER TYPE DIGICON
DATE ACQUIRED OCT 19, 1972

PROCESSING

1. EXPONENTIAL GAIN RATE 4 db/Sec RATE 0-4.000 Sec.
2. VERTICAL STACK
3. NORMAL MOVEOUT INPUT FUNCTION
7. T.A. SELECTION MULTICHANNEL DECON
S.P. 820-625 NO. FILTERS 1 WHITE NOISE 1%
FILTER LENGTH 304
DESIGN RATES NEAR OFFSET 0.500-4.900 Sec
DESIGN RATES FAR OFFSET 2.600-4.900 Sec

3. SINGLE TRACE DISPLAY 8. COMMON DEPTH POINTS 24
9. SELECTION ANALYSIS 10. SELECTION ANALYSIS
11. EQUAL NORMAL MOVEOUT 12. EQUAL AMPLITUDE EQUALIZATION
13. COMMON DEPTH POINT LATERAL 14. AUTO-CORRECTION
15. FILTER LENGTH
DESIGN RATES NEAR OFFSET
DESIGN RATES FAR OFFSET

REVISIONS
REVISION NO. 1
REVISION DATE 10/20/72
REVISION BY [Signature]
REVISION DESCRIPTION [Signature]

PROCESSED BY
digicon inc
HOUSTON, TEXAS

RESERVATO

SEZIONE IDROCARBURI
#1 N. 201
29 LUG. 1974
[Signature]
Postiz