

SICILY GROUP-AMOCO
 LINE ZC-318
 SP 155-40

SOUTHEAST

LINE ZC-318

SHOTPOINTS 155-40


PROJECT SICILY GROUP-AMOCO

FIELD DATA
 RECORDING INSTRUMENTS TI DFS III
 GAIN INFORMATION BINARY
 RECORDING FILTERS 8-18/62 Hz
 SAMPLE RATE 4 MS
 CRATE SIZE 50 METERS
 NUMBER OF TRACES 48
 SEPARATION 205.8 METERS
 CRATE LENGTH 100 METERS
 CRATE WIDTH 25 METERS
 RECORDING METHOD AIRGUN
 MADE BY DIGICON INC
 DATE 9-15-72

PROCESSING
 1 EXPONENTIAL GAIN RATE 4 db/Sec GATE 0-4.000Sec
 2 VERTICAL STACK
 6 NORMAL MINERET INPUT ALLOCATION

7 DECON BEFORE STACK
 155-40
 FILTER LENGTH 200
 DENOD GATES NEAR OFFSET 1.000-4.900 MS
 DENOD GATES FAR OFFSET 3.000-4.900 MS
 8 MINIMA DEPTH POINT NUM 24 FOLD
 9 DATA AFTER STACK
 11 TRACERAMP TIME EQUALIZATION
 12 AUTO-CORRELATION
 155-40
 FILTER LENGTH 200
 DENOD GATES FAR OFFSET 500-4.900 MS
 DENOD GATES NEAR OFFSET 500-4.900 MS

10 FILTERS
 HZ 40 40 100 500
 HZ 10 30 100 200
 HZ 5 25 100 2000 5000

PROCESSED BY

 HOUSTON, TEXAS

