


MARCA DI BOLLO
IDROCARBURI CANALE
DI SICILIA S.p.A.
34
28

Area di subsidenza recente - Zona di margine di un paleoalto miocenico



SEFEL	DATE PROCESSED APRIL '78			
SEFEL J & ASSOCIATES LTD	REEL NUMBER 1293			
SEISMIC DATA PROCESSING	CONTRACT NUMBER 407			
LONDON ENGLAND				
FIELD RECORDING				
RECORDED BY GEOPHYSICAL OFFSHORE EXPLORATION M.V. GOEL EGEDI				
DATE 20TH -28TH JAN 1978 SYSTEM LRS-888 COBAI				
FORMAT SEG 'C' PE GAIN FLOATING POINT				
ENERGY SOURCE AIR GUNS ARRAY 2x8 GUNS 2438 cu.in				
DESCRIPTION 2000 PSI DEPTH 25 ft				
STREAMER 2400 m No TRACES 48				
DEPTH 35 to 45 f. GROUP INTERVAL 50 m				
ARRAY MULTIDYNE GEOPH/PTR OVER				
PARAMETERS RECORDING FOLD 4800 % SP SPACING 25 m				
SAMPLE INTERVAL 2 ms RECORD LENGTH 5 seconds				
RECORDING FILTER Lo 6tr. 18db/OCT HI 124 Hz 75 db / OCT				
POSITIONING SYSTEM - PRIMARY DECOUPLER RESPONDER SECONDARY SATNAV				
DIGITAL PROCESSING				
SEQ	PROCESS	PARAMETERS		
1	DEMULITPLEX	WITH GAIN CURVE & RECOVERY, GAIN CURVE IS DERIVED BY 1.05 ^(1+1/20LOG10T) /28		
2	COT SORT	WITH SURSAMPLING FROM 2 TO 4 ms		
3	DECONVOLUTION	WITH CONSTANT SCALING, SEC BELOW		
4	VELOCITY ANALYSIS	CONSTANT VELOCITY STACKS		
5	NMO CORRECTION			
6	MUTE			
7	HORIZONTAL STACK	48 FOLD		
8	DECONVOLUTION	WITH CONSTANT SCALING		
9	FILTER	TIME VARIANT, SEE BELOW		
10	EQUALIZATION	12 EXPANDING WINDOWS		
11	DISPLAY	SEE BELOW FOR PLOT SCALES		
DECON	# OPERATOR LENGTHS	PREDICTIVE GAP	GENERATION WINDOWS	APPLICATION WINDOWS
3	240	24	0-3000 NEAR TR.	WHOLE TRACE
8	300	32	0-3000 BELOW SEA	WHOLE TRACE
FILTER	CUT OFF 5 ms	6 ms	CUT OFF ALL SPs	APPLICATION TIMES FOR SHOTPOINTS SPECIFIED
9	5	8	55 58 0-1200	
	3	6	40 43 2700-5000	
			BELLOW SEA BOTTOM	
ALL TIMES IN MILLISECOND. ALL FREQUENCIES IN HERTZ FILTERS INTERPOLATED LINEARLY BETWEEN APPLICATION TIMES APPLICATION TIMES INTERPOLATED LINEARLY BETWEEN SHOTPOINTS OPERATOR LENGTH GIVEN IS ACTIVE LENGTH ADD GAP FOR TOTAL LENGTH				
SAMPLE RATE 4 ms DATUM CORRECTION 0 SCALES Horizontal 1:25,000 Vertical 5 cm/sec RECORDING POLARITY COMPRESSION IS-VE N° gives black peak PROCESSING POLARITY POSITIVE N° gives black peak				