



THE AQUAPULSE SYSTEM

LINE DR-546A

S.P. 19 to S.P. 37

DATUM PLANE : SEA LEVEL

RECORDING DATA		PROCESSING INFORMATION		PROCESSING SEQUENCE		LEGEND	
PARTY No 62 ENERGY SOURCE AQUAPULSE FILTER HI/62-LO/8 CABLE 48 GROUPS - 2400 mt. GEOPHONES 20 CRYSTAL ELEMENT EVENLY SPACED 1,52 mt. APART LEAD IN 285 mt. AMPLIFIER S.D.S. BINARY GAIN CHARGE SIZE 4 GUN POPS GUN DEPTH 9.0 mt. AVG. CABLE DEPTH 9.0 mt. DATE SHOT DEC. 1972		SAMPLE RATE 4 ms DECON BEFORE STACK TIME VAR. MIN. PHASE INVERSE FILTER AUTO CORR. INT.: 2 ZONES SEARCH ZONE: 32 ms. TO 200 ms. OPERATOR LENGTH: SEARCH ZONE TIME ZONE: 0-5.0 SEC ITERATIONS: 1		TIME VARIANT FILTER TIME ZONE Hz dB/OCT Hz dB/OCT VARIABLE 15 18 50 48 " 10 12 45 48 " 8 12 35 48 " 7 12 30 48		LINE S.P. INTERSECTION: FUNCTION No. VELOCITY APPLIED: V VELOCITY ANALYSIS: SHOT POINT NO.: 100 WATER DEPTH IN METRES: 10	

DR-546A S.P. 21 V DR-546A S.P. 21 V

DR-546A S.P. 37 V DR-546A S.P. 37 V

SOUTH EAST

