

CR-9 - 84  
S.P. 90 TO S.P. 254

750% DBS-RAP

POLARITY NORMAL


VP 120.00			
TIME	RMS VEL	DIX INT	
0.03	1990	1990	
0.52	2150	2159	
0.68	2250	2548	
0.93	2360	2636	
1.21	2500	2917	
1.39	2600	3192	
1.52	2710	3686	
1.61	2800	4027	
2.35	3120	3722	
3.26	3520	4387	
3.88	3650	4269	

VP 145.50			
TIME	RMS VEL	DIX INT	
0.04	1990	1990	
0.41	2190	2211	
0.70	2430	2734	
1.09	2730	3199	
1.35	2880	3438	
1.43	2980	4332	
1.74	3130	3745	
2.28	3350	4083	
2.79	3620	4500	
3.31	3850	4903	
3.94	3930	4326	

VP 175.00			
TIME	RMS VEL	DIX INT	
0.04	1990	1990	
0.66	2200	2213	
0.81	2310	2742	
0.91	2410	3103	
1.06	2550	3273	
1.27	2680	3258	
1.52	2990	4227	
1.95	3230	3964	
2.95	3640	4329	
3.85	3920	4723	

VP 213.00			
TIME	RMS VEL	DIX INT	
0.02	1960	1980	
0.39	2140	2148	
0.69	2300	2493	
0.97	2460	2816	
1.09	2590	3466	
1.26	2690	3259	
1.60	2870	3456	
1.86	3130	4404	
2.06	3320	4735	
2.82	3550	4109	
3.79	3830	4547	

VP 234.00			
TIME	RMS VEL	DIX INT	
0.02	1970	1970	
0.65	2240	2248	
1.05	2430	2710	
1.14	2550	3671	
1.28	2700	3702	
1.67	3090	3801	
2.48	3350	4044	
3.65	3620	4134	



## SNIA

### WESTERN RICERCHE GEOFISICHE MILAN - ITALY

AREA ITALIA ZONA 4  
PERMESSO CRETAGNA

DATE SHOT ..... JULY 1984  
DATE PROCESSED ..... OCTOBER 1984

RECORDING DATA	PROCESSING SEQUENCE
PARTY NUMBER.....S.I.R.G. 03 RECORDER.....DFS-5 GRAB.....A.G.C RECORDING FILTER (HZ).....12/128 NOTCH FILTER.....50 HZ RECORD LENGTH.....65SEC SAMPLE RATE (MS).....2 SUBSURFACE COVERAGE.....750 PCT GROUP INTERVAL (METERS).....30 NUMBER OF GROUPS.....60 WEATHERING VELOCITY.....500M/S STATIC COMPUTATION VELOCITY.....2000 M/S DATUM PLANE (ABOVE SEA LEVEL).....0	EDIT GEO.AMPL. SR 2MS LEN. 6SEC. INSTR. & GEOPH. PHASE CORRECT. GEOMETRICAL SPREADING GAIN PREPROCESSOR/DECON DECON TYPE MINIMUM PHASE INVERSE FILTER MIN. PRED. DIST 2MS. MAX. PRED. DIST. 130MS NO. OF WINDOWS 1 STRIP AUTOCORRELATION 2.0SEC. SURFACE CONSISTENT RESID. STATICS. VELOCITY ANALYSIS NMO, STATICS, MUTE APPLICATION STRETCH DEPENDENT MUTE 140PCT SURFACE CONSISTENT RESID. STATICS. C.O.P. CONSISTENT RESID. STATICS. MAXIMUM SHIFT: 12 MS STACK REEL N. 104866 TIME VARIANT FILTER NO. FILTERS ARE INTERPOLATED BOTH SPATIALLY AND TEMPORALLY. TIMES AND FILTERS SPECIFIED APPLY AT BEGINNING OF LINE. TIME FILTERS SLOPES 0.050 16-96 HZ 24-72 DB 4.500 12-60 HZ 24-48 DB PLAYBACK HORIZONTAL SCALE 8.33 TR/C VERTICAL SCALE 20 CM/SEC

**SPREAD DIMENSIONS**

**SEISMOMETER ARRAY**

X = 50 M Y = 10 M

ENERGY SOURCE ESPLOSIVO  
SHOT HOLES/S.P. 1  
AVERAGE CHARGE/SHOT 6KG  
AVERAGE SHOT DEPTH 23 M

**LEGEND**

☐ VELOCITY ANALYSIS  
▼ INTERSECTIONS

ANALYST *GR. PEDI* DATE *X-84*

